

Cable Harness, Input/Output (I/O) P/N 83-132483-0XX

FEATURES

- For Use with Kidde Off Road Vehicle Systems
- -40°F (-40°C) to 194°F (90°C) Operating Range
- Quick Connect Connectors
- Ingress Protected
- CE Approved

DESCRIPTION

The Input/Output (I/O) Cable Harness provides a factory made alternative to field fabricating the wiring of various circuits for either the SA1 panel or the Network Control Module.

The I/O Cable Harness may be used for the following circuits:

- Manual Release
- Supervisory
- Protractor Release
- Notification Appliance

Kidde offers the I/O Cable Harness in various nominal lengths, which all afford compatible interconnection. Kidde wraps the harness's connectors to the cable's outer jacket in heat shrink for ingress protection.

ORDERING INFORMATION

Description	Part Number
I/O Cable, 2-ft length	83-132482-002
I/O Cable, 3-ft length	83-132482-003
I/O Cable, 6-ft length	83-132482-006
I/O Cable, 10-ft length	83-132482-010
I/O Cable, 25-ft length	83-132482-025
I/O Cable, 50-ft length	83-132482-050

REFERENCED COMPONENTS

Description	Reference Data Sheet
SA1 Panel	K-83-206
Network Control Module	K-83-207

All trademarks are the property of their respective owners.

This literature is provided for informational purposes only. Kidde-Fenwal, Inc. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly. The technical data contained herein is limited strictly for informational purposes only. Kidde-Fenwal, Inc. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. If you need more information on this product, or if you have a particular problem or question, contact Kidde-Fenwal, Inc.




Figure 1. Cable Harness, Input/Output