Component Description

Warning Nameplate

Designed for use with Clean Agent Systems

FEATURES

• Approved for use with Clean Agent Systems

P/N: WK-218270-000

The Warning Nameplate is mounted inside the protected hazard. It applies to extinguishing agents such as:

- FM-200[®] (HFC-227ea) Agent
- 3M[™] Novec[™] 1230 Fire Protection Fluid
- Inert Gas Agents



• Material: Aluminum Type 1100-H13, 0.032 thick

Note: All characters to be 75 pt. Alternate Gothic #2, all letters to be recessed 0.003 to 0.005 and painted with red chip proof enamel

- Color: No. 21105 per Fed. Std. 595
- Approximate Weight: 3 oz.
- · Finish: One coat clear lacquer both sides

All trademarks are the property of their respective owners.

This literature is provided for informational purposes only. KIDDE-FENWAL, INC. believes this data to be accurate, but it is published and presented without any guarantee or warranty whatsoever. KIDDE-FENWAL, INC. assumes no responsibility for the product's suitability for a particular application. The product must be properly applied to work correctly. If you need more information on this product, or if you have a particular problem or question, contact KIDDE-FENWAL, INC., Ashland, MA 01721 USA. Telephone: (508) 881-2000.

©2017 Kidde-Fenwal, Inc.

This document does not contain any export controlled technical data.

Kidde Fire Systems 400 Main Street Ashland, MA 01721 USA Ph: 508.881.2000 Fax: 508.881.8920 www.kiddefiresystems.com



Effective: March 2017 **K-85-9000 Rev AA**